## NSN 5320-00-974-1132

Blind Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-00-974-1132

Hexad Height: Between 0.086 inches and 0.096 inches Shank Diameter: Between 0.163 inches and 0.164 inches Shank Style: Threaded self-plugging shank w/sleeve Expansion Device: Serrated stem-type w Lubrication: Wax or dry film Grip Length: Between 0.156 inches and 0.219 inches Width Across Flats: Between 0.244 inches and 0.250 inches Heat Treatment: Annealed Material: Steel comp 4130 body or steel comp 8740 body or steel comp 4140 body Material Specification: Mill-s-6758 military specification 1st material response stem or mill-s-6049 military specification 2nd material response stem or mill-s-6626 military specification 3rd material response stem Surface Treatment Specification: Cqrp-416, type 2, cl 3 federal specification single treatment response stem Shaft Life: N/a Unit Of Measure:	
Head Style: Hexagon Head Height: Between 0.88 inches and 0.096 inches Shank Diameter: Between 0.163 inches and 0.164 inches Shank Style: Threaded self-plugging shank wisleeve Expansion Device: Serrated stem-type w Lubrication: Wax or dry film Grip Length: Between 0.156 inches and 0.219 inches Width Across Flats: Between 0.244 inches and 0.250 inches Heat Treatment: Annealed Material: Steel comp 41:30 body or steel comp 87:40 body or steel comp 41:40 body Material Specification 1st material response stem or mil-s-60:49 military specification 2nd material response stem or mil-s-60:68 military specification 3rd material response stem Surface Treatment: Cadmium stem Surface Treatment Specification: Qq-p-116, type 2, cl 3 federal specification single treatment response stem Sheft Life: N\a Unit of Measure: Demilitarization: No Filig: A040a0 Mil-std (military Standard):	Fastener Length:
Hexad Height: Between 0.086 inches and 0.096 inches Shank Diameter: Between 0.163 inches and 0.164 inches Shank Style: Threaded self-plugging shank w/sleeve Expansion Device: Serrated stem-type w Lubrication: Wax or dry film Grip Length: Between 0.156 inches and 0.219 inches Width Across Flats: Between 0.244 inches and 0.250 inches Heat Treatment: Annealed Material: Steel comp 4130 body or steel comp 8740 body or steel comp 4140 body Material Specification: Mill-s-6758 military specification 1st material response stem or mil-s-6049 military specification 2nd material response stem or mil-s-5626 military specification 3rd material response stem Surface Treatment Specification: Cqrp-416, type 2, cl 3 federal specification single treatment response stem Sheff Life: N/a Unit Of Measure: Demilitar/station: No Flig: A040406 Mil-std (military Standard):	Between 0.278 inches and 0.308 inches
Head Height: Between 0.086 inches and 0.096 inches Shank Diameter: Between 0.163 inches and 0.164 inches Shank Style: Threaded self-plugging shank wisleeve Expansion Device: Serrated stem-type w Lubrication: Wax or dry film Grip Length: Between 0.156 inches and 0.219 inches Wildth Across Flats: Between 0.156 inches and 0.250 inches Heat Treatment: Annealed Material: Steel comp 4130 body or steel comp 8740 body or steel comp 4140 body Material Specification: Mil-s-6758 military specification 1st material response stem or mil-s-6049 military specification 2nd material response stem or mil-s-6826 military specification 3rd material response stem Surface Treatment Specification: Qq-p-416, type 2, cl 3 federal specification single treatment response stem Surface Treatment Specification: Unit of Measure:	Head Style:
Between 0.086 inches and 0.096 inches  Shank Diameter: Between 0.163 inches and 0.164 inches  Shank Style: Threaded self-plugging shank w/sleeve  Expansion Device: Serrated stem-type w  Lubrication: Wax or dry film  Grip Length: Between 0.156 inches and 0.219 inches  Width Across Flats: Between 0.156 inches and 0.250 inches  Heat Treatment: Annealed  Material: Steel comp 4130 body or steel comp 8740 body or steel comp 4140 body  Material Specification 1st material response stem or miles-6049 military specification 2nd material response stem or miles-5626 military specification 3rd material response stem  Surface Treatment: Cadmium stem  Surface Treatment Specification:  Oq:p-416, type 2, cl 3 federal specification single treatment response stem  Shelf Life: Na  Unit Of Measure: Demilitarization: No  Fig: A040a0  Mil-std (military Standard):	Hexagon
Shank Diameter: Between 0.163 inches and 0.164 inches Shank Style: Threadd self-plugging shank w/sleeve Expansion Device: Serrated stem-type w Lubrication: Wax or dry film Grip Length: Between 0.156 inches and 0.219 inches Width Across Flats: Between 0.156 inches and 0.219 inches Width Across Flats: Between 0.244 inches and 0.250 inches Heat Treatment: Annealed Material: Steel comp 4130 body or steel comp 8740 body or steel comp 4140 body Material Specification: Mil-s-6758 military specification 1st material response stem or mil-s-6049 military specification 2nd material response stem or mil-s-5626 military specification 3rd material response stem Surface Treatment: Cadmium stem Surface Treatment Specification: Qu-p-416, type 2, cl 3 federal specification single treatment response stem Sheft Life: Na Unit Of Measure: Demilitarization: No Fig: A040a0 Mil-std (military Standard):	Head Height:
Between 0.163 inches and 0.164 inches Shank Style: Threaded self-plugging shank w/sleeve Expansion Device: Serrated stem-type w Lubrication: Wax or dry film Grip Length: Between 0.156 inches and 0.219 inches Wildth Across Flats: Between 0.244 inches and 0.250 inches Heat Treatment: Annealed Material: Steel comp 4130 body or steel comp 8740 body or steel comp 4140 body Material: Steel comp 4130 body or steel comp 8740 body or steel comp 4140 body Material Specification: Milliary specification 3rd material response stem or mil-s-6049 military specification 2nd material response stem or mil-s-5626 military specification 3rd material response stem Surface Treatment: Cadmium stem Surface Treatment Specification: Qq-p-416, type 2, cl 3 federal specification single treatment response stem Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig: A040a0 Mil-std (military Standard):	Between 0.086 inches and 0.096 inches
Shank Style: Threaded self-plugging shank w/sleeve Expansion Device: Serrated stem-type w Lubrication: Wax or dry film Grip Length: Between 0.156 inches and 0.219 inches Width Across Flats: Between 0.244 inches and 0.250 inches Heat Treatment: Annealed Material: Steel comp 4130 body or steel comp 8740 body or steel comp 4140 body Material Specification: Mil-s-6758 military specification 1st material response stem or mil-s-6049 military specification 2nd material response stem or mil-s-5626 military specification 3rd material response stem Surface Treatment: Cadmium stem Surface Treatment Specification: Qq-p-416, type 2, cl 3 federal specification single treatment response stem Shelf Life: N/a Unit Of Measure: Demilitarization: No Fitig: A040a0 Mil-std (military Standard):	Shank Diameter:
Threaded self-plugging shank w/sleeve  Expansion Device: Serrated stem-type w  Lubrication:  Wax or dry film  Grip Length: Between 0.156 inches and 0.219 inches  Width Across Flats: Between 0.244 inches and 0.250 inches  Heat Treatment: Annealed  Material: Steel comp 4130 body or steel comp 8740 body or steel comp 4140 body  Material Specification:  Mil-s-6758 military specification 1st material response stem or mil-s-6049 military specification 2nd material response stem or mil-s-5626 military specification 3rd material response stem  Surface Treatment: Cadmium stem  Surface Treatment Specification:  Qcp-416, type 2, cl 3 federal specification single treatment response stem  Shelf Life: N/a  Unit Of Measure:  Demilitarization:  No  Fig: A040a0  Mil-std (military Standard):	Between 0.163 inches and 0.164 inches
Expansion Device: Serrated stem-type w Lubrication: Wax or dry film Grip Length: Between 0.156 inches and 0.219 inches Width Across Flats: Between 0.244 inches and 0.250 inches Heat Treatment: Annealed Material: Steel comp 4130 body or steel comp 8740 body or steel comp 4140 body Material: Steel comp 4130 body or steel comp 8740 body or steel comp 4140 body Material Specification: Mil-s-6758 military specification 1st material response stem or mil-s-6049 military specification 2nd material response stem or mil-s-5626 military specification 3rd material response stem Surface Treatment: Cadmium stem Surface Treatment Specification: Qq-p-416, type 2, cl 3 federal specification single treatment response stem Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A040a0 Mil-std (military Standard):	Shank Style:
Serrated stem-type w  Lubrication:  Wax or dry film  Grip Length:  Between 0.156 inches and 0.219 inches  Width Across Flats:  Between 0.244 inches and 0.250 inches  Heat Treatment:  Annealed  Material:  Steel comp 4130 body or steel comp 8740 body or steel comp 4140 body  Material Specification:  Mil-s-6758 military specification 1st material response stem or mil-s-6049 military specification 2nd material response stem or mil-s-5626  military specification 3rd material response stem  Surface Treatment: Cadmium stem  Surface Treatment Specification:  Qq-p-416, type 2, cl 3 federal specification single treatment response stem  Shelf Life:  N/a  Unit Of Measure:  —  Demilitarization:  No  Flig: A040a0  Mil-setd (military Standard):	Threaded self-plugging shank w/sleeve
Lubrication:  Wax or dry film  Grip Length:  Between 0.156 inches and 0.219 inches  Width Across Flats:  Between 0.244 inches and 0.250 inches  Heat Treatment:  Annealed  Material:  Steel comp 4130 body or steel comp 8740 body or steel comp 4140 body  Material Specification:  Mil-s-6758 military specification 1st material response stem or mil-s-6049 military specification 2nd material response stem or mil-s-5626 military specification 3rd material response stem  Surface Treatment:  Cadmium stem  Surface Treatment Specification:  Qq-p-416, type 2, cl 3 federal specification single treatment response stem  Shelf Life:  N/a  Unit Of Measure:  Demilitarization:  No  Filig:  A040a0  Mil-std (military Standard):	Expansion Device:
Wax or dry film  Grip Length: Between 0.156 inches and 0.219 inches  Width Across Flats: Between 0.244 inches and 0.250 inches  Heat Treatment: Annealed  Material: Steel comp 4130 body or steel comp 8740 body or steel comp 4140 body  Material Specification: Mill-s-6758 military specification 1st material response stem or mil-s-6049 military specification 2nd material response stem or mill-s-5626 military specification 3rd material response stem  Surface Treatment: Cadmium stem  Surface Treatment Specification: Qq-p-416, type 2, cl 3 federal specification single treatment response stem  Shelf Life: N/a  Unit Of Measure: Demilitarization: No Fiig: A040a0  Mill-std (military Standard):	Serrated stem-type w
Grip Length: Between 0.156 inches and 0.219 inches  Width Across Flats: Between 0.244 inches and 0.250 inches  Heat Treatment: Annealed  Material: Steel comp 4130 body or steel comp 8740 body or steel comp 4140 body  Material Specification: Mil-s-6758 military specification 1st material response stem or mil-s-6049 military specification 2nd material response stem or mil-s-5626 military specification 3rd material response stem  Surface Treatment: Cadmium stem  Surface Treatment Specification: Qq-p-416, type 2, cl 3 federal specification single treatment response stem  Shelf Life: N/a  Unit Of Measure: Demilitarization: No Fiig: A040a0  Mil-std (military Standard):	Lubrication:
Between 0.156 inches and 0.219 inches  Width Across Flats: Between 0.244 inches and 0.250 inches  Heat Treatment: Annealed  Material: Steel comp 4130 body or steel comp 8740 body or steel comp 4140 body  Material Specification:  Mil-s-6758 military specification 1st material response stem or mil-s-6049 military specification 2nd material response stem or mil-s-5626 military specification 3rd material response stem  Surface Treatment: Cadmium stem  Surface Treatment Specification:  Qq-p-416, type 2, cl 3 federal specification single treatment response stem  Shelf Life: N/a  Unit Of Measure:   Demilitarization: No  Fiig: A040a0  Mil-std (military Standard):	Wax or dry film
Width Across Flats: Between 0.244 inches and 0.250 inches Heat Treatment: Annealed Material: Steel comp 4130 body or steel comp 8740 body or steel comp 4140 body Material Specification: Mil-s-6758 military specification 1st material response stem or mil-s-6049 military specification 2nd material response stem or mil-s-5626 military specification 3rd material response stem Surface Treatment: Cadmium stem Surface Treatment Specification: Qq-p-416, type 2, cl 3 federal specification single treatment response stem Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig: A040a0 Mil-std (military Standard):	Grip Length:
Between 0.244 inches and 0.250 inches  Heat Treatment:  Annealed  Material:  Steel comp 4130 body or steel comp 8740 body or steel comp 4140 body  Material Specification:  Mil-s-6758 military specification 1st material response stem or mil-s-6049 military specification 2nd material response stem or mil-s-5626 military specification 3rd material response stem  Surface Treatment: Cadmium stem  Surface Treatment Specification:  Qq-p-416, type 2, cl 3 federal specification single treatment response stem  Shelf Life: N/a  Unit Of Measure:  Demilitarization:  No  Fiig: A040a0  Mil-std (military Standard):	Between 0.156 inches and 0.219 inches
Heat Treatment: Annealed  Material: Steel comp 4130 body or steel comp 8740 body or steel comp 4140 body  Material Specification: Mil-s-6758 military specification 1st material response stem or mil-s-6049 military specification 2nd material response stem or mil-s-5626 military specification 3rd material response stem or mil-s-5626 military specification 3rd material response stem  Surface Treatment: Cadmium stem  Surface Treatment Specification: Qq-p-416, type 2, cl 3 federal specification single treatment response stem  Shelf Life: N/a  Unit Of Measure: Demilitarization: No  Fig: A040a0  Mil-std (military Standard):	Width Across Flats:
Annealed  Material:  Steel comp 4130 body or steel comp 8740 body or steel comp 4140 body  Material Specification:  Mill-s-6758 military specification 1st material response stem or mill-s-6049 military specification 2nd material response stem or mill-s-5626 military specification 3rd material response stem  Surface Treatment:  Cadmium stem  Surface Treatment Specification:  Qq-p-416, type 2, cl 3 federal specification single treatment response stem  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:  A040a0  Mil-std (military Standard):	Between 0.244 inches and 0.250 inches
Material: Steel comp 4130 body or steel comp 8740 body or steel comp 4140 body  Material Specification: Mil-s-6758 military specification 1st material response stem or mil-s-6049 military specification 2nd material response stem or mil-s-5626 military specification 3rd material response stem  Surface Treatment: Cadmium stem  Surface Treatment Specification: Qq-p-416, type 2, cl 3 federal specification single treatment response stem  Shelf Life: N/a  Unit Of Measure: Demilitarization: No  Fiig: A040a0  Mil-std (military Standard):	Heat Treatment:
Steel comp 4130 body or steel comp 8740 body or steel comp 4140 body  Material Specification:  Mil-s-6758 military specification 1st material response stem or mil-s-6049 military specification 2nd material response stem or mil-s-5626 military specification 3rd material response stem  Surface Treatment:  Cadmium stem  Surface Treatment Specification:  Qq-p-416, type 2, cl 3 federal specification single treatment response stem  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:  A040a0  Mil-std (military Standard):	Annealed
Material Specification:  Mil-s-6758 military specification 1st material response stem or mil-s-6049 military specification 2nd material response stem or mil-s-5626 military specification 3rd material response stem  Surface Treatment:  Cadmium stem  Surface Treatment Specification:  Qq-p-416, type 2, cl 3 federal specification single treatment response stem  Shelf Life:  N/a  Unit Of Measure:  Demilitarization:  No  Fiig:  A040a0  Mil-std (military Standard):	Material:
Mil-s-6758 military specification 1st material response stem or mil-s-6049 military specification 2nd material response stem or mil-s-5626 military specification 3rd material response stem  Surface Treatment: Cadmium stem  Surface Treatment Specification: Qq-p-416, type 2, cl 3 federal specification single treatment response stem  Shelf Life: N/a  Unit Of Measure:  Demilitarization: No  Fiig: A040a0  Mil-std (military Standard):	Steel comp 4130 body or steel comp 8740 body or steel comp 4140 body
military specification 3rd material response stem  Surface Treatment: Cadmium stem  Surface Treatment Specification: Qq-p-416, type 2, cl 3 federal specification single treatment response stem  Shelf Life: N/a Unit Of Measure: Demilitarization: No  Fiig: A040a0  Mil-std (military Standard):	Material Specification:
Surface Treatment: Cadmium stem Surface Treatment Specification: Qq-p-416, type 2, cl 3 federal specification single treatment response stem Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A040a0 Mil-std (military Standard):	Mil-s-6758 military specification 1st material response stem or mil-s-6049 military specification 2nd material response stem or mil-s-5626
Cadmium stem  Surface Treatment Specification:  Qq-p-416, type 2, cl 3 federal specification single treatment response stem  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:  A040a0  Mil-std (military Standard):	military specification 3rd material response stem
Surface Treatment Specification:  Qq-p-416, type 2, cl 3 federal specification single treatment response stem  Shelf Life:  N/a  Unit Of Measure: Demilitarization:  No  Fiig: A040a0  Mil-std (military Standard):	Surface Treatment:
Qq-p-416, type 2, cl 3 federal specification single treatment response stem  Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A040a0 Mil-std (military Standard):	Cadmium stem
Shelf Life:  N/a  Unit Of Measure:  Demilitarization:  No  Fiig:  A040a0  Mil-std (military Standard):	Surface Treatment Specification:
N/a Unit Of Measure: Demilitarization: No Fiig: A040a0 Mil-std (military Standard):	Qq-p-416, type 2, cl 3 federal specification single treatment response stem
Unit Of Measure: Demilitarization: No Fiig: A040a0 Mil-std (military Standard):	Shelf Life:
Demilitarization:  No Fiig: A040a0 Mil-std (military Standard):	N/a
No Fiig: A040a0 Mil-std (military Standard):	Unit Of Measure:
No Fiig: A040a0 Mil-std (military Standard):	
Fiig: A040a0 Mil-std (military Standard):	Demilitarization:
A040a0 Mil-std (military Standard):	No
Mil-std (military Standard):	Fiig:
	A040a0
Mil-s-6758 spec.	Mil-std (military Standard):
	Mil-s-6758 spec.