

View Online at <https://aerobasegroup.com/nsn/5320-00-974-1132>

**Fastener Length:**

Between 0.278 inches and 0.308 inches

**Head Style:**

Hexagon

**Head Height:**

Between 0.086 inches and 0.096 inches

**Shank Diameter:**

Between 0.163 inches and 0.164 inches

**Shank Style:**

Threaded self-plugging shank w/sleeve

**Expansion Device:**

Serrated stem-type w

**Lubrication:**

Wax or dry film

**Grip Length:**

Between 0.156 inches and 0.219 inches

**Width Across Flats:**

Between 0.244 inches and 0.250 inches

**Heat Treatment:**

Annealed

**Material:**

Steel comp 4130 body or steel comp 8740 body or steel comp 4140 body

**Material Specification:**

Mil-s-6758 military specification 1st material response stem or mil-s-6049 military specification 2nd material response stem or mil-s-5626 military specification 3rd material response stem

**Surface Treatment:**

Cadmium stem

**Surface Treatment Specification:**

Qq-p-416, type 2, cl 3 federal specification single treatment response stem

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A040a0

**Mil-std (military Standard):**

Mil-s-6758 spec.