## NSN 5320-00-976-3380



Blind Rivet - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5320-00-976-3380 **Thread Class:** За **Thread Direction:** Right-hand **Head Style:** Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer) **Shank Diameter:** Between 0.254 inches and 0.257 inches **Shank Style:** Blind rivet, nut and bolt (assembly) **Head Major Diameter:** 0.3304 inches **Expansion Device:** Threaded sleeve **Grip Length:** 0.375 inches Thready Qty Per Inch (tpi): 32 **Thread Size:** 0.164 inches **Shear Strength:** 125000 single pounds per square inch **Countersink Angle:** 102.0 degrees Material: Steel comp 305 expander **Material Specification:** Qq-s-763 federal specification single material response expander **Surface Treatment:** Cadmium expander **Surface Treatment Specification:** Qq-p-416, ty1, cl3 federal specification single treatment response expander **Thread Series Designator:** Unc Shelf Life: N/a

**Unit Of Measure: Demilitarization:** No Fiig: A040a0

## NSN 5320-00-976-3380

Blind Rivet - Page 2 of 2



Mil-std (military Standard):

Mil-s-18732 spec.