NSN 5320-00-976-3396

Blind Rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-00-976-3396 **Thread Class:** 3b **Thread Direction:** Right-hand Fastener Length: Any acceptable **Head Style:** Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer) **Shank Diameter:** Between 0.380 inches and 0.387 inches **Shank Style:** Blind rivet, nut and bolt (assembly) **Head Major Diameter:** 0.7604 inches **Expansion Device:** Threaded sleeve Fluid Tight Seal Type: O-ring under head **Grip Length:** 0.500 inches Thready Qty Per Inch (tpi): 28 **Thread Size:** 0.250 inches **Shear Strength:** 125000 single pounds per square inch **Countersink Angle:** 100.0 degrees **Seal Material:** Rubber synthetic Material: Steel comp 305 sleeve **Material Specification:** Qq-s-763 federal specification single material response sleeve **Surface Treatment:** Cadmium expander **Surface Treatment Specification:** Qq-p-416 type 1 cl 3 federal specification single treatment response expander **Thread Series Designator:** Unf

Shelf Life:

N/a

NSN 5320-00-976-3396

Blind Rivet - Page 2 of 2



U	n	it	Of	Μe	eas	ur	e:

--

Demilitarization:

No

Fiig:

A040a0

Mil-std (military Standard):

Mil-s-18732 spec.