

View Online at <https://aerobasegroup.com/nsn/5320-00-976-3399>

**Thread Class:**

3b

**Thread Direction:**

Right-hand

**Fastener Length:**

Any acceptable

**Head Style:**

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

**Shank Diameter:**

Between 0.380 inches and 0.387 inches

**Shank Style:**

Blind rivet, nut and bolt (assembly)

**Head Major Diameter:**

0.7604 inches

**Expansion Device:**

Threaded stem

**Fluid Tight Seal Type:**

O-ring under head

**Grip Length:**

0.750 inches

**Thready Qty Per Inch (tpi):**

28

**Thread Size:**

0.250 inches

**Shear Strength:**

125000 single pounds per square inch

**Countersink Angle:**

100.0 degrees

**Seal Material:**

Rubber synthetic

**Material:**

Steel comp 305 sleeve

**Material Specification:**

Qq-s-763 federal specification single material response sleeve

**Surface Treatment:**

Cadmium expander

**Surface Treatment Specification:**

Qq-p-416 type 1 cl 3 federal specification single treatment response expander

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A040a0

**Mil-std (military Standard):**

Mil-s-18732 spec.