NSN 5320-00-977-9001

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-00-977-9001

Thread Class:

Thread Class:
3a
Thread Direction:
Right-hand
Fastener Length:
Between 0.635 inches and 0.660 inches
Head Style:
Err-090
Head Height:
Between 0.058 inches and 0.070 inches
Shank Diameter:
0.2636 inches
Shank Style:
Pin-rivet, tapered, threaded
Head Major Diameter:
Between 0.349 inches and 0.379 inches
Tip Diameter:
0.2590 inches
Lubrication:
Cetyl alcohol
Grip Length:
Between 0.302 inches and 0.317 inches
Thready Qty Per Inch (tpi):
28
Min. Tensile Strength (psi):
180000 pounds per square inch
Thread Size:
0.250 inches
Shear Strength:
108000 single pounds per square inch
Material:
Steel comp 8740 or steel comp e4340
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:
Qq-p-416, type 2, cl 2 federal specification single treatment response
Thread Series Designator:
Unif
Specification Data:
80205-nas1728 professional/industrial association standard
Shelf Life:
N/a

NSN 5320-00-977-9001

Pin-rivet - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A528u0