

View Online at <https://aerobasegroup.com/nsn/5320-00-980-5661>

**Fastener Length:**

Between 0.465 inches and 0.495 inches

**Head Style:**

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

**Shank Diameter:**

Between 0.178 inches and 0.180 inches

**Shank Style:**

Self-plugging high clinch shank

**Head Major Diameter:**

Between 0.296 inches and 0.332 inches

**Expansion Device:**

Serrated stem-type w

**Grip Length:**

Between 0.344 inches and 0.406 inches

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Hardness Rating:**

30.0 rockwell c nut and 45.0 rockwell c nut

**Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

**Material:**

Iron alloy 660 sleeve

**Material Specification:**

Ams 5735 assn standard single material response sleeve or ams 5737 assn standard single material response sleeve

**Surface Treatment:**

Passivate sleeve

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response sleeve

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A040a0