NSN 5320-00-983-0582

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-00-983-0582



Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 0.582 inches and 0.607 inches

Head Style:

Err-090

Head Height:

Between 0.044 inches and 0.056 inches

Shank Diameter:

0.2114 inches

Shank Style:

Pin-rivet, tapered, threaded

Head Major Diameter:

Between 0.312 inches and 0.323 inches

Tip Diameter:

0.2068 inches

Lubrication:

Cetyl alcohol

Grip Length:

Between 0.302 inches and 0.317 inches

Min. Tensile Strength (psi):

180000 pounds per square inch

Thread Size:

0.190 inches

Shear Strength:

108000 single pounds per square inch

Material:

Steel comp 8740 or steel comp 4340

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416, type 2, cl 2 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

NSN 5320-00-983-0582

Pin-rivet - Page 2 of 2

Fiig: A528u0

