

View Online at <https://aerobasegroup.com/nsn/5320-00-984-3362>

Fastener Length:

Between 0.153 inches and 0.183 inches

Head Style:

Hexagon

Head Height:

Between 0.086 inches and 0.096 inches

Shank Diameter:

Between 0.163 inches and 0.165 inches

Shank Style:

Threaded self-plugging shank w/sleeve

Expansion Device:

Serrated stem-type w

Lubrication:

Wax or dry film

Grip Length:

Between 0.031 inches and 0.094 inches

Width Across Flats:

Between 0.277 inches and 0.283 inches

Hardness Rating:

39.0 rockwell c bolt and 43.0 rockwell c bolt

Shear Strength:

1920 double pounds per square inch

Heat Treatment:

Annealed

Material:

Steel comp 304 sleeve or steel comp 303 sleeve or steel comp 303f sleeve

Material Specification:

Qq-s-763 federal specification 1st material response sleeve or ams 5639 assn standard 1st material response sleeve or astm a582 assn standard 2nd material response sleeve or ams 5641 assn standard 3rd material response sleeve

Surface Treatment:

Cadmium sleeve and chromate sleeve and passivate sleeve

Surface Treatment Specification:

Qq-p-416, type 2, cl 2 federal specification single treatment response bolt

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A040a0

Mil-std (military Standard):

Mil-s-6758 spec.