

View Online at <https://aerobasegroup.com/nsn/5320-00-985-5107>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Fastener Length:**

Between 1.4280 inches and 1.4480 inches

**Head Style:**

Err-090

**Head Height:**

Between 0.0980 inches and 0.1080 inches

**Width Between Flats:**

0.1250 inches

**Shank Diameter:**

Between 0.3110 inches and 0.3120 inches

**Shank Style:**

Pin-rivet, straight, threaded

**Head Major Diameter:**

Between 0.4720 inches and 0.5020 inches

**Grip Length:**

Between 0.9330 inches and 0.9430 inches

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Thread Size:**

0.3120 inches

**Material:**

Steel comp 4130 or steel comp 4140 or steel comp 8740

**Material Specification:**

Mil-s-6758 military specification 1st material response or mil-s-5626 military specification 2nd material response or mil-s-6049 military specification 3rd material response

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Qq-p-416, type 1, cl 3 federal specification single treatment response

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A528u0

**Mil-std (military Standard):**

Mil-s-6758 spec.