

View Online at <https://aerobasegroup.com/nsn/5320-00-985-5107>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 1.4280 inches and 1.4480 inches

Head Style:

Err-090

Head Height:

Between 0.0980 inches and 0.1080 inches

Width Between Flats:

0.1250 inches

Shank Diameter:

Between 0.3110 inches and 0.3120 inches

Shank Style:

Pin-riquet, straight, threaded

Head Major Diameter:

Between 0.4720 inches and 0.5020 inches

Grip Length:

Between 0.9330 inches and 0.9430 inches

Min. Tensile Strength (psi):

160000 pounds per square inch

Thread Size:

0.3120 inches

Material:

Steel comp 4130 or steel comp 4140 or steel comp 8740

Material Specification:

Mil-s-6758 military specification 1st material response or mil-s-5626 military specification 2nd material response or mil-s-6049 military specification 3rd material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416, type 1, cl 3 federal specification single treatment response

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-s-6758 spec.