# NSN 5320-00-985-5121

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-00-985-5121



#### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

### Fastener Length:

Between 0.9900 inches and 1.0100 inches

#### Head Style:

Err-090

#### **Head Height:**

Between 0.0550 inches and 0.0600 inches

#### Width Between Flats:

0.0780 inches

#### Shank Diameter:

Between 0.1615 inches and 0.1635 inches

#### Shank Style:

Pin-rivet, straight, threaded

#### Head Major Diameter:

Between 0.3060 inches and 0.3220 inches

#### Grip Length:

Between 0.6830 inches and 0.6930 inches

### **Features Provided:**

Washer

#### Thready Qty Per Inch (tpi):

32

#### Min. Tensile Strength (psi):

160000 pounds per square inch

#### Thread Size:

0.1640 inches

#### Material:

Steel comp 4130 bolt or steel comp 4140 bolt or steel comp 8740 bolt

## Material Specification:

Mil-s-7720 military specification single material response collar or qq-s-763 federal specification single material response collar

## Surface Treatment:

Cadmium bolt

# Surface Treatment Specification:

Qq-s-763 federal specification single treatment response collar

# **Thread Series Designator:**

Unc

# Shelf Life:

N/a

## Unit Of Measure:

---

# NSN 5320-00-985-5121

Pin-rivet - Page 2 of 2

Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-s-6758 spec.

