NSN 5320-00-988-2544

Blind Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-00-988-2544

Fastener Length:

0.168 inches

Head Style:

Hexagon

Head Height:

0.096 inches

Shank Diameter:

Between 0.162 inches and 0.164 inches

Shank Style:

Threaded self-plugging shank w/sleeve

Expansion Device:

Threaded stem

Grip Length:

Between 0.031 inches and 0.092 inches

Width Across Flats:

Between 0.244 inches and 0.250 inches

Hardness Rating:

39.0 rockwell c nut and 43.0 rockwell c nut

Material:

Steel comp 304 sleeve or steel comp 303f sleeve or steel comp 303 sleeve

Material Specification:

Qq-s-763 federal specification 1st material response sleeve or ams 5639 assn standard 1st material response sleeve or ams 5641 assn

standard 2nd material response sleeve or astm a582 assn standard 3rd material response sleeve

Surface Treatment:

Cadmium sleeve and passivate sleeve

Surface Treatment Specification:

Qq-p-416, ty2, cl2 federal specification single treatment response bolt

Specification Data:

80205-nas1669 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A040a0

Mil-std (military Standard):

Mil-s-5626 spec.