

View Online at <https://aerobasegroup.com/nsn/5320-00-989-7598>

**Fastener Length:**

Between 0.276 inches and 0.306 inches

**Head Style:**

Hexagon

**Head Height:**

Between 0.103 inches and 0.113 inches

**Shank Diameter:**

Between 0.202 inches and 0.203 inches

**Shank Style:**

Threaded self-plugging shank w/sleeve

**Expansion Device:**

Serrated stem-type w

**Lubrication:**

Dry film

**Grip Length:**

Between 0.156 inches and 0.219 inches

**Width Across Flats:**

Between 0.305 inches and 0.312 inches

**Min. Tensile Strength (psi):**

180000 pounds per square inch

**Hardness Rating:**

39.0 rockwell c nut and 43.0 rockwell c nut

**Heat Treatment:**

Annealed

**Material:**

Steel comp 304 sleeve or steel comp 303f sleeve or steel comp 303 sleeve

**Material Specification:**

Qq-s-763 federal specification 1st material response sleeve or ams 5639 assn standard 1st material response sleeve or ams 5614 assn standard 2nd material response sleeve or astm a582 assn standard 3rd material response sleeve

**Surface Treatment:**

Cadmium sleeve and passivate sleeve

**Surface Treatment Specification:**

Qq-p-416, type 2, cl 2 federal specification single treatment response nut

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A040a0

**Mil-std (military Standard):**

Mil-s-5626 spec.