

View Online at <https://aerobasegroup.com/nsn/5320-00-989-7598>

Fastener Length:

Between 0.276 inches and 0.306 inches

Head Style:

Hexagon

Head Height:

Between 0.103 inches and 0.113 inches

Shank Diameter:

Between 0.202 inches and 0.203 inches

Shank Style:

Threaded self-plugging shank w/sleeve

Expansion Device:

Serrated stem-type w

Lubrication:

Dry film

Grip Length:

Between 0.156 inches and 0.219 inches

Width Across Flats:

Between 0.305 inches and 0.312 inches

Min. Tensile Strength (psi):

180000 pounds per square inch

Hardness Rating:

39.0 rockwell c nut and 43.0 rockwell c nut

Heat Treatment:

Annealed

Material:

Steel comp 304 sleeve or steel comp 303f sleeve or steel comp 303 sleeve

Material Specification:

Qq-s-763 federal specification 1st material response sleeve or ams 5639 assn standard 1st material response sleeve or ams 5614 assn standard 2nd material response sleeve or astm a582 assn standard 3rd material response sleeve

Surface Treatment:

Cadmium sleeve and passivate sleeve

Surface Treatment Specification:

Qq-p-416, type 2, cl 2 federal specification single treatment response nut

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A040a0

Mil-std (military Standard):

Mil-s-5626 spec.