## NSN 5320-00-993-8847

Solid Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-00-993-8847

3
Fastener Length:
Between 0.302 inches and 0.322 inches
Head Style:
Universal
Head Height:
Between 0.080 inches and 0.090 inches
Shank Diameter:
Between 0.186 inches and 0.191 inches
Shank Style:
Straight
Head Major Diameter:
Between 0.356 inches and 0.394 inches
Grip Length:
Between 0.021 inches and 0.041 inches
Shear Strength:
25000 single pounds per square inch
Material:
Steel comp 301 or steel comp 302 or steel comp 303 or steel comp 303f or steel comp 303s or steel comp 303se or steel comp 304 or
steel comp 304l or steel comp 305 or steel comp 308 or steel comp 309 or steel comp 309s or steel comp 310 or steel comp 310s or
steel comp 314 or steel comp 316 or steel comp 316l or steel comp 317 or steel comp 321 or steel comp 323 or steel comp 324 or steel
comp 347 or steel comp 348 or steel comp 385
Material Specification:
66 federal standard all material responses
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:
Qq-p-416, type 2, cl 3 federal specification single treatment response and qq-p-35 federal specification 1st treatment response
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A040a0