

View Online at <https://aerobasegroup.com/nsn/5320-00-994-7079>

Fastener Length:

Between 0.365 inches and 0.385 inches

Head Style:

Universal

Head Height:

Between 0.054 inches and 0.064 inches

Shank Diameter:

Between 0.124 inches and 0.128 inches

Shank Style:

Straight

Head Major Diameter:

Between 0.238 inches and 0.262 inches

Grip Length:

Between 0.177 inches and 0.197 inches

Shear Strength:

25000 single pounds per square inch

Material:

Steel comp 301 or steel comp 302 or steel comp 303 or steel comp 303f or steel comp 303s or steel comp 303se or steel comp 304 or steel comp 304l or steel comp 305 or steel comp 308 or steel comp 309 or steel comp 309s or steel comp 310 or steel comp 310s or steel comp 314 or steel comp 316 or steel comp 316l or steel comp 317 or steel comp 321 or steel comp 323 or steel comp 324 or steel comp 347 or steel comp 348 or steel comp 385

Material Specification:

66 federal standard all material responses

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416, type 2, cl 3 federal specification single treatment response and qq-p-35 federal specification 1st treatment response

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A040a0