NSN 5320-00-995-8258

Tubular Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-00-995-8258

Fastener Length:

Between 0.305 inches and 0.319 inches

Head Style:

Oval/truss

Head Height:

Between 0.030 inches and 0.038 inches

Hole Diameter:

Between 0.084 inches and 0.088 inches

Shank Diameter:

Between 0.118 inches and 0.123 inches

Shank Style:

Tubular

Head Major Diameter:

Between 0.213 inches and 0.223 inches

Hole Depth:

Between 0.078 inches and 0.110 inches

Shear Strength:

32000 double pounds per square inch

Material:

Steel comp 1005 or steel comp 1006 or steel comp 1008 or steel comp 1009 or steel comp 1010 or steel comp 1011 or steel comp 1012 or steel comp 1013 or steel comp 1015 or steel comp 1016 or steel comp 1017 or steel comp 1018 or steel comp 1019 or steel comp

1020 or steel comp 1021 or steel comp 1022

Material Specification:

66 federal standard all material responses

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416, type 2, cl 2 federal specification single treatment response

Specification Or Standard:

12 type and e grade and 3 class

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A040a0