

View Online at <https://aerobasegroup.com/nsn/5320-00-997-0008>

Head Style:

Flush countersunk

Shank Diameter:

0.156 inches

Shank Style:

Err-090

Head Major Diameter:

Between 0.220 inches and 0.258 inches

Grip Length:

Between 0.126 inches and 0.188 inches

Features Provided:

Casehardened

Hardness Rating:

36.0 rockwell c and 40.0 rockwell c

Shear Strength:

95000 single pounds per square inch

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Material:

Steel comp 4130 or steel comp 4140 or steel comp 8630 or steel comp 4130 or steel comp 6150 or steel comp 4037

Material Specification:

Mil-s-6758 military specification 1st material response or mil-s-5626 military specification 2nd material response or mil-s-6050 military specification 3rd material response or mil-s-6050 military specification 4th material response or mil-s-6758 military specification 5th material response or mil-s-8503 military specification 6th material response or ams 6300 assn standard 7th material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416, type 2, cl 3 federal specification single treatment response

Specification Data:

80205-nas525 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-s-6758 spec.