NSN 5320-01-004-1994

Blind Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-01-004-1994

Fastener Length:
Between 0.347 inches and 0.377 inches
Head Style:
Universal
Head Height:
Between 0.035 inches and 0.043 inches
Shank Diameter:
Between 0.124 inches and 0.128 inches
Shank Style:
Pull through hollow shank
Head Major Diameter:
Between 0.360 inches and 0.390 inches
Expansion Device:
Plain stem-type t
Grip Length:
Between 0.126 inches and 0.250 inches
Shear Strength:
280 single pounds per square inch
Material:
Steel
Material Specification:
66 comp 1006 through 1010 and comp 1030 through 1060 federal standard single material response
Surface Treatment:
Zinc or cadmium or phosphate
Surface Treatment Specification:
Qq-z-325 type 2 class 3 federal specification 1st treatment response or qq-p-416 type 2 class 3 federal specification 2nd treatment response
or mil-p-16232 type z class 2 military specification 3rd treatment response or mil-p-16232 type z class 4b military specification 3rd treatment
response
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A040a0
Mil-std (military Standard):
Mil-p-16232 spec.