NSN 5320-01-004-4226

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-004-4226



Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 3.0210 inches and 3.0460 inches

Head Style:

Flush countersunk

Shank Diameter:

0.6537 inches

Shank Style:

Pin-rivet, tapered, threaded

Head Major Diameter:

Between 0.8880 inches and 0.9710 inches

Tip Diameter:

0.6407 inches

Lubrication:

Cetyl alcohol

Grip Length:

Between 0.9950 inches and 1.0050 inches

Thready Qty Per Inch (tpi):

18

Min. Tensile Strength (psi):

180000 pounds per square inch

Thread Size:

0.5625 inches

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Material:

Steel

Surface Treatment:

Cadmium or chromate

Surface Treatment Specification:

Qq-p-416, type 2, cl 2 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

NSN 5320-01-004-4226

Pin-rivet - Page 2 of 2

Fiig: A528u0

