

View Online at <https://aerobasegroup.com/nsn/5320-01-004-9131>

Fastener Length:

Between 0.517 inches and 0.547 inches

Head Style:

Universal

Head Height:

Between 0.062 inches and 0.082 inches

Shank Diameter:

Between 0.186 inches and 0.190 inches

Shank Style:

Pull through hollow shank

Head Major Diameter:

Between 0.600 inches and 0.650 inches

Expansion Device:

Plain stem-type t

Grip Length:

Between 0.250 inches and 0.375 inches

Material:

Steel comp 1030 mandrel or steel comp 1033 mandrel or steel comp 1034 mandrel or steel comp 1035 mandrel or steel comp 1536 mandrel or steel comp 1037 mandrel or steel comp 1038 mandrel or steel comp 1039 mandrel or steel comp 1040 mandrel or steel comp 1541 mandrel or steel comp 1042 mandrel or steel comp 1043 mandrel or steel comp 1044 mandrel or steel comp 1045 mandrel or steel comp 1046 mandrel or steel comp 1548 mandrel or steel comp 1049 mandrel or steel comp 1050 mandrel or steel comp 1551 mandrel or steel comp 1552 mandrel or steel comp 1053 mandrel or steel comp 1055 mandrel or steel comp 1059 mandrel or steel comp 1060 mandrel

Material Specification:

66 federal standard all material responses mandrel

Surface Treatment:

Zinc mandrel or cadmium mandrel or phosphate mandrel

Surface Treatment Specification:

Qq-z-325 type 2 cl 3 federal specification 1st treatment response mandrel or qq-p-416 federal specification 2nd treatment response mandrel and mil-p-16232 ty z cl 2 military specification 2nd treatment response mandrel or mil-p-16232 ty z cl 4 military specification 2nd treatment response mandrel

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A040a0

Mil-std (military Standard):

Mil-p-16232 spec.