

View Online at <https://aerobasegroup.com/nsn/5320-01-005-3238>

Fastener Length:

Between 0.160 inches and 0.190 inches

Head Style:

Universal

Head Height:

Between 0.030 inches and 0.040 inches

Shank Diameter:

Between 0.124 inches and 0.128 inches

Shank Style:

Self-plugging

Head Major Diameter:

Between 0.238 inches and 0.262 inches

Expansion Device:

Knob stem-type k

Grip Length:

Between 0.040 inches and 0.062 inches

Shear Strength:

280 single pounds per square inch

Material:

Steel comp 1030 mandrel or steel comp 1033 mandrel or steel comp 1034 mandrel or steel comp 1035 mandrel or steel comp 1536 mandrel or steel comp 1037 mandrel or steel comp 1038 mandrel or steel comp 1039 mandrel or steel comp 1040 mandrel or steel comp 1541 mandrel or steel comp 1042 mandrel or steel comp 1043 mandrel or steel comp 1044 mandrel or steel comp 1045 mandrel or steel comp 1046 mandrel or steel comp 1548 mandrel or steel comp 1049 mandrel or steel comp 1050 mandrel or steel comp 1551 mandrel or steel comp 1552 mandrel or steel comp 1053 mandrel or steel comp 1055 mandrel or steel comp 1059 mandrel or steel comp 1060 mandrel

Surface Treatment:

Zinc mandrel and chromate mandrel or cadmium mandrel or cadmium mandrel and chromate mandrel or cadmium mandrel and phosphate mandrel or phosphate zinc mandrel

Surface Treatment Specification:

Qq-z-325, type 2, cl 3 federal specification 1st treatment response mandrel or qq-p-416 federal specification 2nd treatment response mandrel or qq-p-416 military specification 1st treatment response mandrel or qq-p-416 federal specification 4th treatment response mandrel or mil-p-16232, ty z, cl 2 or 4 military specification 5th treatment response mandrel

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A040a0

Mil-std (military Standard):

Mil-p-16232 spec.