# NSN 5320-01-006-3965

Solid Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-01-006-3965

# Fastener Length:

Between 1.115 inches and 1.135 inches

#### Head Style:

Undersized oval countersunk

# Head Height:

Between 0.004 inches and 0.006 inches

#### Shank Diameter:

Between 0.186 inches and 0.189 inches

### Shank Style:

Straight

Head Major Diameter:

Between 0.275 inches and 0.302 inches

#### Head Minor Diameter:

Between 0.198 inches and 0.208 inches

#### **Countersink Height:**

0.046 inches

Shear Strength:

26000 single pounds per square inch

#### **Countersink Angle:**

Between 99.5 degrees and 100.5 degrees

### Material:

Aluminum alloy 2117

#### **Material Specification:**

Qq-a-430 federal specification single material response

#### Surface Treatment:

Anodize or chromate

# Surface Treatment Specification:

Mil-a-8625 military specification 1st treatment response or mil-c-5541 military specification 2nd treatment response

#### **Specification Data:**

80205-nas1097 professional/industrial association standard

#### Shelf Life:

N/a

# Unit Of Measure:

```
--
```

#### Demilitarization:

No

# Fiig:

A040a0

# Mil-std (military Standard):

Mil-a-8625 spec.