

View Online at <https://aerobasegroup.com/nsn/5320-01-006-7022>

General Description:

Steel, mil-s-5000 or mil-s-5026 or mil-s-6049 pin, fin. Cadmium, qq-p-416, type 1, cl 3 and cetyl alcohol lubricant, grip diameter 0.1885 in. Min and 0.1895 in. Max, max grip lg 0.438 in., flush countersunk head w/ chamfer, incl angle 100.0 deg, head diameter 0.3765 in. Min and 0.3813 in. Max, head h 0.0785 in. Min and 0.0805 in. Max, pin-rivet thd shank, thd 0.190-32 unjf 3a rh, thd lg 0.325 in. Nom, hex. Socket thd end w across flats 0.0791 in. Min and 0.0806 in. Max, double shear str 5380 lb, min tensile str 160000 psi, steel, qq-s-764, type 303se collar, fin. Cadmium, qq-p-416, type 1, cl 3 and cetyl alcohol lubricant, thd 0.190-32 unjf 3b rh, collar h 0.437 in. Min and 0.457 in. Max, collar od 0.303 in. Min and 0.307 in. Max, collar id 0.192 in. Min and 0.200 in. Max, aluminum alloy, qq-a-250/4, t6 or qq-a-250/5, t6 washer, fin. Anodized, mil-a-8625, washer od 0.340 in. Nom, washer thk 0.010 in. Nom

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No