

View Online at <https://aerobasegroup.com/nsn/5320-01-006-7024>

**General Description:**

Steel, mil-s-5000 or mil-s-5626 or mil-s-6049 pin, fin. Cadmium, qq-p-416, type 1, cl 3 and cetyl alcohol lubricant, grip diameter 0.2485 in. Min and 0.2495 in. Max, max grip lg 0.312 in., flat chamfer head, head diameter 0.415 in. Min and 0.440 in. Max, head h 0.077 in. Min and 0.090 in. Max, pin-rivet thd shank, thd 0.250-28 unjf 3a rh, thd lg 0.395 in. Nom, hex. Socket thd end, w across flats 0.0947 in. Min and 0.0967 in. Max, socket dp 0.130 in. Min and 0.150 in. Max, double shear str 9300 lb, min tensile str 160000 psi, steel, qq-s-764, type 303se collar, fin. Cadmium, qq-p-416, type 1, cl 3 and cetyl alcohol lubricant, thd 0.250-28 unjf 3b rh, collar h 0.532 in. Min and 0.552 in. Max, collar od 0.408 in. Min and 0.412 in. Max, collar id 0.252 in. Min and 0.261 in. Max, cres, mil-s-5059, type 302 washer, fin. Cadmium, qq-p-416, type 1, cl 3, washer od 0.442 in. Nom, washer thk 0.010 in. Nom

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No