

View Online at <https://aerobasegroup.com/nsn/5320-01-006-7028>

**Thread Class:**

Aal

**Thread Direction:**

Right-hand

**Fastener Length:**

Between 0.6270 inches and 0.6470 inches

**Head Style:**

Err-090

**Head Height:**

Between 0.0640 inches and 0.0740 inches

**Width Between Flats:**

0.0780 inches

**Shank Diameter:**

Between 0.1885 inches and 0.1895 inches

**Shank Style:**

Pin-riquet, straight, threaded

**Head Major Diameter:**

Between 0.3570 inches and 0.3770 inches

**Grip Length:**

Between 0.3070 inches and 0.3170 inches

**Thready Qty Per Inch (tpi):**

32

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Thread Size:**

0.1900 inches

**Material:**

Steel comp 4130 or steel comp 4140 or steel comp 8740

**Material Specification:**

Mil-s-6758 military specification 1st material response or mil-s-5626 military specification 2nd material response or mil-s-6049 military specification 3rd material response

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Qq-p-416, type 1, cl 3 federal specification single treatment response

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A528u0

**Mil-std (military Standard):**

Mil-s-6758 spec.