

View Online at <https://aerobasegroup.com/nsn/5320-01-006-7032>

General Description:

Steel, mil-s-5000 or mil-s-5626 or mil-s-6049 pin, fin. Cadmium, qq-p-416, type 1, cl 3 and cetyl alcohol lubricant, grip diameter 0.2485 in. Min and 0.2495 in. Max, max grip lg 0.562 in., head diameter 0.387 in. Min and 0.412 in. Max, head h 0.059 in. Min and 0.047 in. Max, thd 0.250-28 unjf 3a rh, thd lg 0.395 in. Nom, hex. Socket thd end, w across flats 0.0947 in. Min and 0.0967 in. Max, socket dp 0.130 in. Min and 0.150 in. Max, double shear str 9300 lb, single shear str 95000 psi, aluminum alloy, qq-a-430, 2024 or qq-a-225/6 collar, thd 0.250-28 unjf 3b rh, collar h0.532 in. Min and 0.552 in. Max, collar od 0.408 in. Min and 0.412 in. Max, collar id 0.252 in. Min and 0.261 in. Max, anodized, mil-a-8625, cetyl lubricant, heat treatment t6 mil-h-6088, flat chamfer head style, pin-rivet thd shank style

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No