

View Online at <https://aerobasegroup.com/nsn/5320-01-006-7039>

General Description:

Tsteel, mil-s-5000 or mil-s-5626 or mil-s-6049 pin, fin. Cadmium, qq-p-416, type 1, cl 3 and cetyl alcohol lubricant, grip diameter 0.1885 in. Min and 0.1895 in. Max, max grip lg 0.125 in., flat chamfer head, head diameter 0.357 in. Min and 0.377 in. Max, head h 0.064 in. Min and 0.074 in. Max, pin-rivet thd shank, thd 0.190-32 unjf 3a rh, thd lg 0.325 in. Nom, hex. Socket thd end, w across flats 0.0791 in. Min and 0.0806 in. Max, socket dp 0.115 in. Min and 0.135 in. Max, double shear str 5380 lb, min tensile str 160000 psi, steel, qq-s-764, type 303se collar, fin. Cadmium, qq-p-416, type 1, cl 3 and cetyl alcohol lubricant, thd 0.190-32 unjf 3b rh, collar h 0.437 in. Min and 0.457 in. Max, collar od 0.303 in. Min and 0.307 in. Max, collar id 0.192 in. Min and 0.200 in. Max

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No