

View Online at <https://aerobasegroup.com/nsn/5320-01-006-7040>

General Description:

Steel, mil-s-5000 or mil-s-5626 or mil-s-6049 pin, fin. Cadmium, qq-p-416, type 1, cl 3 and cetyl alcohol lubricant, grip diameter 0.1625 in. Min and 0.1635 in. Max, max grip lg 0.688 in., head diameter 0.242 in. Min and 0.262 in. Max, head h 0.037 in. Min and 0.047 in. Max, thd 0.164-32 unjc 3a rh, thd lg 0.312 in. Nom, hex. Socket thd end, w across flats 0.0791 in. Min and 0.0801 in. Max, socket dp 0.115 in. Min and 0.135 in. Max, double shear str 4010 lb, single shear str 95000 psi, aluminum alloy, qq-a-430, 2024 or qq-a-225/6 collar, thd 0.164-32 unjc 3b rh, collar h 0.427 in. Min and 0.447 in. Max, collar od 0.288 in. Min and 0.292 in. Max, collar id 0.166 in. Min and 0.173 in. Max, anodized, mil-a-8625, cetyl lubricant, heat treatment t6 mil-h-6088, flat chamfer head style, pin-rivet thd shank style

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No