

View Online at <https://aerobasegroup.com/nsn/5320-01-006-7041>

**General Description:**

Steel, mil-s-5000 or mil-s-5626 or mil-s-6049 pin, fin. Cadmium, qq-p-416, type 1, cl 3 and cetyl alcohol lubricant, grip diameter 0.2485 in. Min and 0.2495 in. Max, max grip lg 0.938 in., flat chamfer head, head diameter 0.415 in. Min and 0.440 in. Max, head h 0.077 in. Min and 0.090 in. Max, pin-rivet thd shank, thd 0.250-28 unjf 3a rh, thd lg 0.395 in. Nom, hex. Socket thd end, w across flats 0.0947 in. Min and 0.0967 in. Max, double shear str 9300 lb min, min tensile str 160000 psi, steel, qq-s-764, type 303se collar, fin. Cadmium, qq-p-416, type 1, cl 3 and cetyl alcohol lubricant, thd 0.250-28 unjf 3b rh, collar h 0.527 in. Min and 0.547 in. Max, self aligning collar, steel, ams 5643 or ams 5528 or ams 5520 washer, washer solution heat treated, fin. Cadmium, qq-p-416, type 1, cl 3, washer od 0.465 in. Min and 0.475 in. Max, washer id 0.303 in. Nom, washer thk 0.110 in. Min and 0.120 in. Max

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No