

View Online at <https://aerobasegroup.com/nsn/5320-01-006-7042>

General Description:

Steel, mil-s-5000 or mil-s-5626 or mil-s-6049 pin, fin. Cadmium, qq-p-416, type 1, cl 3 and cetyl alcohol lubricant, grip diameter 0.1885 in. Min and 0.1895 in. Max, max grip lg 0.312 in., flat chamfer head, head diameter 0.357 in. Min and 0.377 in. Max, head h 0.064 in. Min and 0.074 in. Max, pin-rivet thd shank, thd 0.190-32 unjf 3a rh, thd lg 0.325 in. Nom, hex. Socket thd end, w across flats 0.0791 in. Min and 0.0806 in. Max, double shear str 5380 lb min, min tensile str 160000 psi, steel, qq-s-764, type 303se collar, fin. Cadmium, qq-p-416, type 1, cl 3 and cetyl alcohol lubricant, thd 0.190-32 unjf 3b rh, collar h 0.432 in. Min and 0.452 in. Max, self aligning collar, steel, ams 5643 or ams 5528 or ams 5520 washer, washer solution heat treated, fin. Cadmium, qq-p-416, type 1, cl 3, washer od 0.355 in. Min and 0.365 in. Max, washer id 0.255 in. Nom, washer thk 0.085 in. Min and 0.095 in. Max

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No