NSN 5320-01-006-7045

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-006-7045

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

0.715 inches

Head Style:

Err-090

Head Height:

0.072 inches

Width Between Flats:

0.062 inches

Shank Diameter:

0.187 inches

Shank Style:

Pin-rivet, straight, threaded

Head Major Diameter:

0.368 inches

Lubrication:

Cetyl alcohol

Grip Length:

0.312 inches

Min. Tensile Strength (psi):

160000 pounds per square inch

Thread Size:

0.190 inches

Shear Strength:

5380 double pounds per square inch

Material:

Stainless steel

Material Specification:

Mil-s-5000 military specification single material response or mil-s-5626 military specification single material response or mil-s-6049 military

specification single material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416, type 1, cl 3 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

NSN 5320-01-006-7045

Pin-rivet - Page 2 of 2

Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-s-5000 spec.

