

View Online at <https://aerobasegroup.com/nsn/5320-01-006-7048>

General Description:

Titanium alloy, ams 4928 or ams 4967 pin, grip diameter 0.1890 in. Min and 0.1895 in. Max, max grip lg 0.438 in., head diameter 0.295 in. Min and 0.315 in. Max, head h 0.045 in. Min and 0.055 in. Max, thd 0.190-32 unjf 3a, thd lg 0.325 in. Nom, hex socket thd end, w across flats 0.0791 in. Min and 0.0806 in. Max, socket dp 0.115 in. Min and 0.135 in. Max, cetyl alcohol lubricant, double shear str 5380 lb, single shear str 95000 psi min, aluminum alloy, qq-a-430, 2024 or qq-a-225/6 collar, thd 0.190-32 unjf 3b, rh thd, collar h 0.477 in. Nom, collar od 0.307 in. Max, collar id 0.192 in. Min and 0.200 in. Max, anodized, mil-a-8625, cetyl alcohol lubricant, heat treatment t6, mil-h-6088, aluminum alloy, qq-a-250/8 or qq-a-250/4 or qq-a-250/5 washer, anodized, mil-a-8625, washer od 0.360 in. Nom, washer thk 0.020 in. Nom, flat chamfer head style, pin-rivet thd shank style

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No