

View Online at <https://aerobasegroup.com/nsn/5320-01-006-8899>

**Fastener Length:**

Between 0.313 inches and 0.343 inches

**Head Style:**

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

**Shank Diameter:**

Between 0.123 inches and 0.128 inches

**Shank Style:**

Self-plugging

**Head Major Diameter:**

Between 0.229 inches and 0.243 inches

**Expansion Device:**

Plain stem-type t

**Grip Length:**

Between 0.126 inches and 0.187 inches

**Countersink Angle:**

100.0 degrees

**Material:**

Steel comp 1006 mandrel or steel comp 1008 mandrel or steel comp 1009 mandrel or steel comp 1010 mandrel or steel comp 1012 mandrel or steel comp 1015 mandrel or steel comp 1016 mandrel or steel comp 1017 mandrel or steel comp 1018 mandrel or steel comp 1019 mandrel or steel comp 1020 mandrel or steel comp 1021 mandrel or steel comp 1022 mandrel or steel comp 1023 mandrel or steel comp 1524 mandrel or steel comp 1025 mandrel

**Material Specification:**

Qq-a-430 federal specification single material response body

**Surface Treatment:**

Zinc mandrel or chromate mandrel or phosphate mandrel

**Surface Treatment Specification:**

Qq-z-325 type 2 cl 3 federal specification 1st treatment response mandrel or qq-p-416 federal specification 2nd treatment response mandrel or mil-p-16232 ty z cl 2 military specification 2nd treatment response mandrel or mil-p-16232 ty z cl 4 military specification 2nd treatment response mandrel

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A040a0

**Mil-std (military Standard):**

Mil-c-5541 spec.