
## NSN 5320-01-006-9094

Pin-rivet - Page 1 of 2



## **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

## Fastener Length:

Between 0.475 inches and 0.495 inches

#### Head Style:

Flush countersunk

## Width Between Flats:

Between 0.079 inches and 0.081 inches

## Shank Diameter:

Between 0.1885 inches and 0.1895 inches

#### Shank Style:

Pin-rivet, straight, threaded

## Head Major Diameter:

Between 0.297 inches and 0.302 inches

## Grip Length:

0.255 inches

## Thread Size:

0.190 inches

## Shear Strength:

5380 double pounds per square inch

## Countersink Angle:

100.0 degrees

## **Special Features:**

Single shear strength 95000

#### Material:

Titanium alloy

#### **Material Specification:**

Ams 4928 assn standard single material response or ams 4967 assn standard single material response

#### Surface Treatment:

Aluminum

### Surface Treatment Specification:

294, fscm 73197 mfr ref single treatment response

## **Thread Series Designator:**

Unjf

Shelf Life:

N/a

## Unit Of Measure:

--

## Demilitarization:

No



# NSN 5320-01-006-9094

Pin-rivet - Page 2 of 2

**Fiig:** A528u0

