NSN 5320-01-006-9497

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-006-9497

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 1.590 inches and 1.610 inches

Head Style:

Flush countersunk

Width Between Flats:

Between 0.127 inches and 0.130 inches

Shank Diameter:

Between 0.3170 inches and 0.3175 inches

Shank Style:

Head Major Diameter:

Between 0.469 inches and 0.474 inches

Grip Length:

1.010 inches

Thready Qty Per Inch (tpi):

24

Thread Size:

0.312 inches

Shear Strength:

95000 single pounds per square inch

Countersink Angle:

100.0 degrees

Material:

Titanium alloy

Material Specification:

Ams 4928 assn standard single material response or ams 4967 assn standard single material response

Surface Treatment:

Anodize

Surface Treatment Specification:

Ti-shield 3 mfr ref 1st treatment response or tiodize type 2 fscm 73197 mfr ref 2nd treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

NSN 5320-01-006-9497

Pin-rivet - Page 2 of 2

Fiig: A528u0

