
# NSN 5320-01-006-9498

Pin-rivet - Page 1 of 2





## **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

## Fastener Length:

Between 1.877 inches and 1.897 inches

# Head Style:

Flush countersunk

## Width Between Flats:

Between 0.079 inches and 0.081 inches

# Shank Diameter:

Between 0.1885 inches and 0.1895 inches

#### Shank Style:

Pin-rivet, straight, threaded

#### Head Major Diameter:

Between 0.297 inches and 0.302 inches

### Grip Length:

1.567 inches

# Thready Qty Per Inch (tpi):

32

# Thread Size:

0.190 inches

# Shear Strength:

125000 single pounds per square inch

#### **Countersink Angle:**

100.0 degrees

# Material:

Steel comp 431

#### **Material Specification:**

Mil-s-18732 military specification single material response

#### Surface Treatment:

Cadmium

#### **Surface Treatment Specification:**

Qq-p-416, type 2, cl 3 federal specification single treatment response

# **Thread Series Designator:**

Unjf

# Shelf Life:

N/a

# Unit Of Measure:

--

# Demilitarization:

No

# NSN 5320-01-006-9498

Pin-rivet - Page 2 of 2

**Fiig:** A528u0

Mil-std (military Standard):

Mil-s-18732 spec.

