NSN 5320-01-007-7092

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-007-7092 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 1.303 inches and 1.323 inches **Head Style:** Flush countersunk **Head Height:** Between 0.102 inches and 0.112 inches Width Between Flats: Between 0.1270 inches and 0.1295 inches **Shank Diameter:** Between 0.3115 inches and 0.3120 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.472 inches and 0.502 inches **Grip Length:** 1.317 inches Thready Qty Per Inch (tpi): 36 **Thread Size:** 0.164 inches **Shear Strength:** 125000 single pounds per square inch **Countersink Angle:** 100.0 degrees Material: Titanium alloy **Material Specification:** Ams 4928 assn standard single material response or ams 4967 assn standard single material response **Surface Treatment:** Cadmium **Surface Treatment Specification:** Qq-p-416, type 2, cl 3 federal specification single treatment response **Thread Series Designator:** Unjc Shelf Life: N/a

Unit Of Measure:

NSN 5320-01-007-7092

Pin-rivet - Page 2 of 2



_						
11	em)	 tor	172	+ 1	nn	

No

Fiig:

A528u0