## NSN 5320-01-007-8247

Solid Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-01-007-8247

View Online at https://aerobasegroup.com/nsn/5320-01-007-8247
Fastener Length:
Between 1.365 inches and 1.385 inches
Head Style:
Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)
Shank Diameter:
Between 0.093 inches and 0.097 inches
Shank Style:
Straight w/radius chamfered tip
Head Major Diameter:
Between 0.175 inches and 0.183 inches
Grip Length:
1.224 mils and 1.244 centimeters
Shear Strength:
26000 single pounds per square inch
Countersink Angle:
Between 99.5 degrees and 100.5 degrees
Heat Treatment:
T-4 solution heat treated
Material:
Aluminum alloy 2117
Material Specification:
Ams 7222 assn standard single material response
Surface Treatment:
Anodize or oxide film
Surface Treatment Specification:
Mil-a-8625 military specification 1st treatment response or mil-c-5541 military specification 2nd treatment response
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A040a0

A040a0

Mil-std (military Standard):

Mil-a-8625 spec.