
## NSN 5320-01-008-6366

Pin-rivet - Page 1 of 2





#### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

## Fastener Length:

Between 0.815 inches and 0.835 inches

#### Head Style:

Err-090

#### **Head Height:**

Between 0.055 inches and 0.074 inches

#### Width Between Flats:

Between 0.0791 inches and 0.0806 inches

#### Shank Diameter:

Between 0.1885 inches and 0.1895 inches

#### Shank Style:

Pin-rivet, straight, threaded

#### Head Major Diameter:

Between 0.295 inches and 0.315 inches

## Lubrication:

Solid film

## Grip Length:

Between 0.495 inches and 0.505 inches

#### Thready Qty Per Inch (tpi):

32

## Thread Size:

0.190 inches

## **Special Features:**

Collar included

#### Material:

Aluminum alloy 7075

#### **Material Specification:**

Qq-a-225/9 federal specification single material response or qq-a-430 federal specification single material response

#### Surface Treatment:

Anodize

#### Surface Treatment Specification:

Mil-a-8625 military specification single treatment response

#### **Thread Series Designator:**

Unjf

## Shelf Life:

N/a

#### Unit Of Measure:

---

# NSN 5320-01-008-6366

Pin-rivet - Page 2 of 2

Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-a-8625 spec.

