

View Online at <https://aerobasegroup.com/nsn/5320-01-008-9545>

General Description:

Tsteel, mil-s-5000 or mil-s-5626 or mil-s-6049 pin, fin. Cadmium, qq-p-416, type 1, cl 3 and cetyl alcohol lubricant, grip diameter 0.1625 in. Min and 0.1635 in. Max, max grip lg 0.250 in., flat chamfer head, head diameter 0.306 in. Min and 0.322 in. Max, head h 0.055 in. Min and 0.060 in. Max, pin-rivet thd shank, thd 0.164-32 unjc 3a rh, thd lg 0.312 in. Nom, hex. Socket thd end, w across flats 0.0791 in. Min and 0.0801 in. Max, socket dp 0.115 in. Min and 0.135 in. Max, double shear str 4010 lb, min tensile str 160000 psi, steel, qq-s-764, type 303se collar, fin. Cadmium, qq-p-416, type 1, cl 3 and cetyl alcohol lubricant, thd 0.164-32 unjc 3b rh, collar h 0.427 in. Min and 0.447 in. Max, collar od 0.283 in. Min and 0.287 in. Max, collar id 0.166 in. Min and 0.173 in. Max

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No