

View Online at <https://aerobasegroup.com/nsn/5320-01-010-5860>

Thread Class:

2a

Thread Direction:

Right-hand

Head Style:

Hexagon

Head Height:

0.113 inches

Shank Diameter:

Between 0.197 inches and 0.199 inches

Shank Style:

Threaded self-plugging shank w/sleeve

Expansion Device:

Threaded stem

Grip Length:

Between 0.470 inches and 0.531 inches

Width Across Flats:

Between 0.332 inches and 0.346 inches

Thready Qty Per Inch (tpi):

40

Thread Size:

0.138 inches

Material:

Steel comp 304 sleeve or steel comp 303 sleeve or steel comp 303f sleeve

Material Specification:

Qq-s-763 federal specification 1st material response sleeve or ams 5639 assn standard 1st material response sleeve or astm a582 assn standard 2nd material response sleeve or ams 5641 assn standard 3rd material response sleeve

Surface Treatment:

Cadmium sleeve and chromate sleeve and passivate sleeve

Surface Treatment Specification:

Qq-p-416, type 2, cl2 federal specification 1st treatment response sleeve and qq-p-35 federal specification 2nd treatment response sleeve

Thread Series Designator:

Unf

Specification Data:

80205-nas1673 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A040a0

Mil-std (military Standard):

Mil-s-5626 spec.