

View Online at <https://aerobasegroup.com/nsn/5320-01-011-7516>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Fastener Length:**

Between 2.020 inches and 2.040 inches

**Head Style:**

Flush countersunk

**Width Between Flats:**

0.078 inches

**Shank Diameter:**

Between 0.2005 inches and 0.2025 inches

**Shank Style:**

Pin-riquet, straight, threaded

**Head Major Diameter:**

0.386 inches

**Grip Length:**

Between 1.939 inches and 2.000 inches

**Thready Qty Per Inch (tpi):**

56

**Min. Tensile Strength (psi):**

180000 pounds per square inch

**Thread Size:**

0.164 inches

**Shear Strength:**

108000 single pounds per square inch

**Countersink Angle:**

100.0 degrees

**Special Features:**

Pull stem type with hex socket in head

**Material:**

Steel comp 8740

**Material Specification:**

Aisi assn standard single material response

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Qq-p-416, type 2, cl 2 federal specification single treatment response

**Thread Series Designator:**

Unjs

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A528u0