# NSN 5320-01-013-4022

Solid Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-01-013-4022

# Fastener Length:

Between 0.365 inches and 0.385 inches

# Head Style:

Undersized oval countersunk

# Head Height:

Between 0.004 inches and 0.006 inches

# Shank Diameter:

Between 0.249 inches and 0.252 inches

#### Shank Style:

Straight

Head Major Diameter:

Between 0.371 inches and 0.395 inches

# Head Minor Diameter:

Between 0.316 inches and 0.326 inches

# **Countersink Height:**

0.060 inches

Shear Strength:

33000 single pounds per square inch

# Countersink Angle:

100.0 degrees

# Heat Treatment:

T-4 solution heat treated

### Material:

Aluminum alloy 2017

# **Material Specification:**

Qq-a-430, t4 federal specification single material response

# Surface Treatment:

Anodize or chromate

# Surface Treatment Specification:

Mil-a-8625 military specification 1st treatment response or mil-c-5541 military specification 2nd treatment response

# **Specification Data:**

80205-nas1097 professional/industrial association standard

#### Shelf Life:

N/a

# Unit Of Measure:

--

# Demilitarization:

No

Fiig:

A040a0

# Mil-std (military Standard):

Mil-a-8625 spec.