
## NSN 5320-01-014-4374

Pin-rivet - Page 1 of 2





#### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

#### Fastener Length:

Between 1.365 inches and 1.385 inches

#### Head Style:

Err-090

#### Head Height:

Between 0.068 inches and 0.078 inches

#### Width Between Flats:

Between 0.1270 inches and 0.1295 inches

#### Shank Diameter:

Between 0.311 inches and 0.312 inches

#### Shank Style:

Pin-rivet, straight, threaded

#### Head Major Diameter:

Between 0.475 inches and 0.505 inches

#### End Application:

W/s: aircraft, thunderbolt ii, a-10

#### Grip Length:

0.880 inches

#### Thready Qty Per Inch (tpi):

24

### Thread Size:

0.312 inches

Material:

Steel comp h11

## Material Specification:

Ams 6487 assn standard single material response

## Surface Treatment:

Nickel and cadmium

## Surface Treatment Specification:

Ams 2416 assn standard all treatment responses

## **Thread Series Designator:**

Unjf

Shelf Life:

N/a

#### Unit Of Measure:

--

## Demilitarization:

No

# NSN 5320-01-014-4374

Pin-rivet - Page 2 of 2

**Fiig:** A528u0

