NSN 5320-01-014-4375

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-014-4375 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 1.347 inches and 1.367 inches **Head Style:** Err-090 **Head Height:** Between 0.120 inches and 0.140 inches Width Between Flats: Between 0.1582 inches and 0.1617 inches **Shank Diameter:** Between 0.3735 inches and 0.3745 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.530 inches and 0.600 inches Lubrication: Cetyl alcohol **Grip Length:** 0.817 inches Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 220000 pounds per square inch **Thread Size:** 0.375 inches **Shear Strength:** 29200 double pounds per square inch Material: Steel comp h11 **Material Specification:** Ams 6487 assn standard single material response **Surface Treatment:** Nickel and cadmium **Surface Treatment Specification:** Ams 2416 assn standard all treatment responses **Thread Series Designator:** Unjf Shelf Life:

N/a

NSN 5320-01-014-4375

Pin-rivet - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A528u0