
# NSN 5320-01-016-2807

Pin-rivet - Page 1 of 2





#### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

# Fastener Length:

Between 0.881 inches and 0.906 inches

### Head Style:

Flush countersunk

#### Shank Diameter:

0.4209 inches

#### Head Major Diameter:

0.613 inches

#### Tip Diameter:

0.4154 inches

#### Lubrication:

Cetyl alcohol

# Grip Length:

Between 0.427 inches and 0.442 inches

# Thready Qty Per Inch (tpi):

24

### Min. Tensile Strength (psi):

220000 pounds per square inch

#### **Thread Size:**

0.375 inches

# **Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

#### Material:

Steel comp h11

#### **Material Specification:**

Ams 6487 assn standard single material response

#### **Surface Treatment:**

Nickel and cadmium

#### Surface Treatment Specification:

Ams 2416 assn standard single treatment response

#### **Thread Series Designator:**

Unjf

Shelf Life:

N/a

# Unit Of Measure:

--

# Demilitarization:

No

# NSN 5320-01-016-2807

Pin-rivet - Page 2 of 2

**Fiig:** A528u0

