NSN 5320-01-016-2949



Solid Rivet - Page 1 of 1 View Online at https://aerobasegroup.com/nsn/5320-01-016-2949 Fastener Length: Between 0.490 inches and 0.510 inches **Head Style:** Undersized oval countersunk **Head Height:** Between 0.004 inches and 0.006 inches **Shank Diameter:** Between 0.186 inches and 0.189 inches **Shank Style:** Straight **Head Major Diameter:** Between 0.2749 inches and 0.3016 inches **Head Minor Diameter:** Between 0.198 inches and 0.208 inches **Countersink Height:** 0.046 inches **Shear Strength:** 33000 single pounds per square inch **Countersink Angle:** 100.0 degrees **Heat Treatment:** T-4 solution heat treated Material: Aluminum alloy 2017 **Material Specification:** Qq-a-430 federal specification single material response **Surface Treatment:** Anodize or chromate **Surface Treatment Specification:** Mil-a-8625 military specification 1st treatment response or mil-c-5541 military specification 2nd treatment response **Specification Data:** 80205-nas1097 professional/industrial association standard Shelf Life: N/a **Unit Of Measure:**

A040a0

Mil-std (military St

Demilitarization:

No Fiig:

Mil-std (military Standard):

Mil-a-8625 spec.