

View Online at <https://aerobasegroup.com/nsn/5320-01-016-7574>

**Fastener Length:**

0.787 inches

**Head Style:**

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

**Shank Diameter:**

Between 0.189 inches and 0.193 inches

**Shank Style:**

Self-plugging shank w/grooved end for locking

**Head Major Diameter:**

Between 0.349 inches and 0.357 inches

**Expansion Device:**

Serrated stem-type w

**Grip Length:**

Between 0.563 inches and 0.625 inches

**Shear Strength:**

1090 single pounds per square inch

**Countersink Angle:**

100.0 degrees

**Material:**

Aluminum alloy 5056 body

**Material Specification:**

Qq-a-430 federal specification single material response stem

**Surface Treatment:**

Anodize stem or chromate stem

**Surface Treatment Specification:**

Mil-a-8625 military specification 1st treatment response stem or mil-c-5541 military specification 2nd treatment response stem

**Specification Data:**

80205-nas1921 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A040a0

**Mil-std (military Standard):**

Mil-a-8625 spec.